

HUBER+SUHNER® DATA SHEET

Coaxial Cable: K_02252_D



Description

PTFE - 50 Ohm - double screen

Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.54 mm
Dielectric	PTFE		1.55 mm
Outer conductor	Copper, Silver plated	Braid, 96 %	2 mm
Outer conductor	Copper, Silver plated	Braid, 91 %	2.5 mm
Jacket	FEP	RAL 8015 - br	3 mm +/- 0.1
Print	HUBER+SUHNER K 02252 D 50 Ohm (PA no.)		

Electrical Data

Impedance	50	Ω +/- 2
Max. operating frequency	6	GHz
Capacitance	97	pF/m
Velocity of signal propagation	69	%
Signal delay	4.86	ns/m
Insulation resistance	$\geq 1 \times 10^8$	M Ω m
Min. screening effectiveness	>80	dB (up to 6 GHz)
Max. operating voltage	0.85	kV _{rms} (at sea level)
Test voltage	1.7	kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	2.4	kg/100 m
Min. bending radius	static	18 mm
	repeated (for max. 50 bendings)	30 mm
	dynamic	45 mm

Environmental Data

Temperature range	-20 °C... + 60 °C	-65 °C... + 165 °C
Installation temperature	-20 °C... + 60 °C	
Flammability	IEC 60332-3	
2002/95/EC (RoHS)	compliant	

Ordering Information

Order as K_02252_D

Additional Information

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	crimped (U4)
	clamped (U4)
	soldered —

HUBER+SUHNER® DATA SHEET

Coaxial Cable: K_02252_D



Rev.: G

Matrix **Attenuation** [formula: $(a \cdot f^{0.5} + b \cdot f)$] **and Power CW** [formula: $(p \cdot f^{0.5})$]

Coefficients:

a=	0.7865	b=	0.121	f _{max} =	6	p _{at} 1GHz =	149
	Frequency		Nom. attenuation		Nom. attenuation		Max. CW power
	(GHz)		(dB / m)		(dB / ft)		(watt)
			sea level 25° C ambient temperature		sea level 25° C ambient temperature		sea level 40° C ambient temperature
	0.3		0.47		0.143		272
	0.6		0.68		0.207		192
	0.9		0.86		0.262		157
	1.2		1.01		0.308		136
	1.5		1.14		0.347		122
	1.8		1.27		0.387		111
	2.1		1.39		0.424		103
	2.4		1.51		0.460		96
	2.7		1.62		0.494		91
	3.0		1.73		0.527		86
	3.3		1.83		0.558		82
	3.6		1.93		0.588		79
	3.9		2.03		0.619		75
	4.2		2.12		0.646		73
	4.5		2.21		0.674		70
	4.8		2.30		0.701		68
	5.1		2.39		0.728		66
	5.4		2.48		0.756		64
	5.7		2.57		0.783		62
	6.0		2.65		0.808		61

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
 Phone +41 (0)71 353 41 11
 Fax +41 (0)71 353 45 90
 www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions