

**@irLAN™**



**@irLAN RM-105-8**  
Fiber Optic Splice Closure

## Features

- May be used for cut, uncut and taut sheath applications.
- May be used for all fiber optic cable.
- Sheath retention & central strength member termination system included.
- Ribbed closure construction-lightweight plastic offers strength and resistance to chemical and U.V attack
- Installation and reentry with a minimum of tools
- All hardware are captived
- Closure can be flash tested
- Protection class: IP68
- ROHS compliance
- Base-to-base seals on the closures are mechanical for ease of installation and re-entry
- Cable seals by heat shrink tube

## Application

Watertight, Underground, Aerial, Vault and Wall Mountable.

## Specifications

Model No	Spliced fiber storage capacity(single fusion)	Size(mm) Height x diameter	Cable ports	Max. diameter of cable(mm)
RM-105-8	96 splices (4 x24 splices)	540mm x 180 mm	1 oval port + 8 round ports	1 oval port for 1 cable with max 25 mm. 8 round ports , each port for 1 cable with max 10 mm

**@ir-LAN™**

**Videomax AVS Ltd.**

tel.: +359 – 2 – 827 11 20, +359 – 2 – 927 00 22,  
fax: +359 – 2 – 825 49 27

e-mail: [info@videomaxavs.com](mailto:info@videomaxavs.com)

**[www.videomaxavs.com](http://www.videomaxavs.com)**