

**@irLAN™**



**@irLAN RM105**  
Fiber Optic Splice Closure

## Features

- May be used for cut, uncut and taut sheath applications.
- May be used for all fiber optic cable.
- Sheath retention & central strength member termination system included.
- Ribbed closure construction-lightweight plastic offers strength and resistance to chemical and U.V attack
- Installation and reentry with a minimum of tools
- All hardware are captured

## Sealing way

- Base-to-base seals on the closures are mechanical for ease of installation and re-entry
- Cable seals by heat shrink tube

## Application

Watertight, Underground, Aerial, Vault and Wall Mountable.

@irLAN™



## Specifications

Model No.	Height x Diameter	Spliced fiber storage capacity	Cable ports	Max. diameter of cable(mm)	Splice Trays	Splice Capacity of the tray
@irLAN RM105	540mm x 180mm	standard fiber, 96 cores(4 x 24 splices)	5 ports	1 port : for 1 loop cable with max 25 mm. 4 ports : each port for 1 cable with max 19 mm.	Max .2 trays (24 fibers),	24 fibers

**@ir-LAN™**

**Videomax AVS Ltd.**

tel.: +359 – 2 – 827 11 20, +359 – 2 – 927 00 22,  
fax: +359 – 2 – 825 49 27

e-mail: [info@videomaxavs.com](mailto:info@videomaxavs.com)

**[www.videomaxavs.com](http://www.videomaxavs.com)**